



A powerful, durable and reliable workhorse whose reputation is built on helping you build yours. It's been rigorously tested, beaten up, dropped and pushed to the limits to make sure it will always work when you need it most. The 2235 Series is incredibly powerful, durable and reliable so that it delivers every time you need **REAL WORK** done right.

- 1 220 Nm (900 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Titanium hammercase is lightweight with unparalleled durability.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- FREE two-year limited warranty without tool registration.

Specifications at 6.2 bar (90 psi)

Part Number	2235QTiMAX-2
Ordering number	47517884001
Drive size (square)	1/2 in
Drive length	2 in / 50 mm
Torque settings (forward / reverse)	4 / 1
Other available versions:	
- bare tool	2235QTiMAX
- standard length anvil	2235QTiMAX

PERFORMANCE

Maximum torque in forward	870 ft-lb / 1 180 Nm
Maximum torque in reverse	900 ft-lb / 1 220 Nm
Nut busting torque in reverse	1 300 ft-lb / 1760 Nm
Recommended fastener size	9/16 in / M14
Free speed	8 500 rpm
Impacts per minute	1 220

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	6.0 CFM / 170 L/min
Air consumption at load	24.0 CFM / 680 L/min
Impacting sound pressure / power (ISO15744)	91.9 / 102.9 dB(A)
Free speed sound pressure / power (ISO15744)	88.7 / 99.7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	7.7 / 2.7 m/s²

WEIGHT & DIMENSIONS

Tool weight	5.0 lb / 2.3 kg
Tool dimensions (L x W x H)	244 x 74 x 183 mm
Shipping weight	5.8 lb / 2.6 kg
Shipping dimensions (L x W x H)	201 x 265 x 82 mm
UPC / EAN code	6 63023 12001 0
Origin	Assembled in the USA



2235Q TiMAX-2

ACCESSORIES



SK4M3L

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



SK4M14

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets

For the complete range, see our accessory catalogue.



2235M-BOOT

47520153001

Protective tool boot



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



115-LBK1

04616108

Lubricant kit for Impacttools™ with composite housing



115-4T

04616157

Grease for Impacttools with composite housing



2235-THK1

47517319001

Impact mechanism service kit



SK4M5L

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



SK4M18

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



BMDS-4

92842087

Cable balancer, 2-4 kg, 2 m (6-1/2 ft)



10Z4

03875671

Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.



2235-TK1

47517401001

Motor service kit

0