

# Specification QX Series™



Nm



rpm



kg



mm



mm



V



in




Communication

## QX ETS Cordless Tools (Ergonomic Tightening System)


QXN Cordless Precision Screwdriver								
QXN2PT08ES6	1.6-8	1,150	0.91	203	26	20V Li-ion	3/8" Square	Via USB Cable
QXN2PT08EQ4	1.6-8	1,150	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Via USB Cable
QXN2PT12ES6	2.4-12	750	0.91	203	26	20V Li-ion	3/8" Square	Via USB Cable
QXN2PT12EQ4	2.4-12	750	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Via USB Cable
QXN2PT18ES6	3.6-18	500	0.91	203	26	20V Li-ion	3/8" Square	Via USB Cable
QXN2PT18EQ4	3.6-18	500	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Via USB Cable
QXN2PT24ES6	4.8-24	500	0.91	212	26	20V Li-ion	3/8" Square	Via USB Cable
QXN Cordless Angle Wrench								
QXN2AT27ES6	5.4-27	330	1.68	552	17.2	20V Li-ion	3/8" Square	Via USB Cable
QXN Cordless High Torque Angle Wrench								
QXN5AT40ES08	8.0-40	545	2.27	586.1	21.6	40V Li-ion	1/2" Square	Via USB Cable
QXN5AT80ES08	12.0-80	375	2.27	586.1	21.6	40V Li-ion	1/2" Square	Via USB Cable
QXC Cordless Precision Screwdriver								
QXC2PT08ES6	1.6-8	1,150	0.91	203	26	20V Li-ion	3/8" Square	Via USB Cable
QXC2PT08EQ4	1.6-8	1,150	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Via USB Cable
QXC2PT12ES6	2.4-12	750	0.91	203	26	20V Li-ion	3/8" Square	Via USB Cable
QXC2PT12EQ4	2.4-12	750	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Via USB Cable
QXC2PT18ES6	3.6-18	500	0.91	203	26	20V Li-ion	3/8" Square	Via USB Cable
QXC2PT18EQ4	3.6-18	500	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Via USB Cable
QXC2PT24ES6	4.8-24	500	0.91	212	26	20V Li-ion	3/8" Square	Via USB Cable
QXC Cordless Angle Wrench								
QXC2AT27ES6	5.4-27	330	1.68	552	17.2	20V Li-ion	3/8" Square	Via USB Cable
QXC Cordless High Torque Angle Wrench								
QXC5AT40ES08	8.0-40	545	2.27	586.1	21.6	40V Li-ion	1/2" Square	Via USB Cable
QXC5AT80ES08	12.0-80	375	2.27	586.1	21.6	40V Li-ion	1/2" Square	Via USB Cable
QXX Cordless Precision Screwdriver								
QXX2PT08ES6	1.6-8	1,150	0.91	203	26	20V Li-ion	3/8" Square	Wireless Enabled + USB
QXX2PT08EQ4	1.6-8	1,150	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Wireless Enabled + USB
QXX2PT12ES6	2.4-12	750	0.91	203	26	20V Li-ion	3/8" Square	Wireless Enabled + USB
QXX2PT12EQ4	2.4-12	750	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Wireless Enabled + USB
QXX2PT18ES6	3.6-18	500	0.91	203	26	20V Li-ion	3/8" Square	Wireless Enabled + USB
QXX2PT18EQ4	3.6-18	500	0.91	206.5	26	20V Li-ion	1/4" Quick Change	Wireless Enabled + USB
QXX2PT24ES6	4.8-24	500	0.91	212	26	20V Li-ion	3/8" Square	Wireless Enabled + USB
QXX Cordless Angle Wrench								
QXX2AT27ES6	5.4-27	330	1.68	552	17.2	20V Li-ion	3/8" Square	Wireless Enabled + USB
QXX Cordless High Torque Angle Wrench								
QXX5AT40ES08	8.0-40	545	2.27	586.1	21.6	40V Li-ion	1/2" Square	Wireless Enabled + USB
QXX5AT80ES08	12.0-80	375	2.27	586.1	21.6	40V Li-ion	1/2" Square	Wireless Enabled + USB

## QX Multiplier Reaction Arms

Ingersoll Rand offers the following variety of reaction arms for different applications. Reaction arms are available in both 52 mm and 72 mm spline drives, depending on the size of the gearbox.



Cranked, 45 or 90 degrees



Straight, aluminum or steel (multiple lengths available)







Plate and pin (multiple lengths available)




Double-sided



Sliding slave kit (multiple lengths available)



Sliding peg and yoke assembly (multiple lengths available)



Sliding yoke, paddle and yoke assembly (multiple lengths available)



Blank welding ring