



All purpose angle grinder, suitable for metal dressing, rust removal, weld preparation and automotive bodywork.

- Powerful motor delivers 0.50 kW (0.65 HP).
- Durable aluminum housing withstands tough operating conditions.
- Ergonomic auxiliary handle provides excellent maneuverability.
- Variable-speed lever allows precise delivery of power and speed.
- Integral trigger safety lock prevents accidental tool start.
- Tool delivered with a grinding disc.

Specifications at 6.2 bar (90 psi)

Part Number	LA422-EU
Ordering number	01328582
Wheel type	Type 27
Wheel capacity	5 in / 125 mm
Maximum wheel thickness	1/4 in / 6 mm
Spindle size	3/8"-24
Other available versions:	
- 100 mm (4") wheel capacity	LA421-EU

PERFORMANCE

Rated power	0.65 HP / 0.50 kW
Free speed	12 000 rpm

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	6.0 CFM / 170 L/min
Air consumption at load	25.0 CFM / 708 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	85.6 / 98.6 dB(A)
Vibration level / measurement uncertainty (ISO28927)	6.0 / 2.1 m/s ²

WEIGHT & DIMENSIONS

Tool weight	3.78 lb / 1.72 kg
Tool dimensions (L x W x H)	226 x 140 x 84 mm
Shipping weight	5.12 lb / 2.33 kg
Shipping dimensions (L x W x H)	144 x 237 x 107 mm
Origin	Made in Taiwan




IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)


Quick Release Couplings

For the complete range, see our accessory catalogue.


CO-1315

56753106

Hose clamps, 13-15 mm outside diameter, 100 pcs


67-LBK1

04637344

Lubricant kit for angle head tools


67-4T

04637336

Grease for high-speed angle heads


77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)


RH-10

92536044

PVC hose, 10 mm inside diameter, 30 m


Filters, regulators, lubricators

For the complete range, see our accessory catalogue.


10Z4

03875671

Oil, Class 1, no. 10, 0.12 L


Lubricants

For the complete range, see our accessory catalogue.