

Air Drills, Screwdrivers and Specialty Tools | Specialty Tools (incl. cutting tools)

325B

Air Nibbler



- Cutting capacity:
1.2 mm (18-gauge, 0.05")
- 4,200 blows per minute
- Variable speed lever

529


Reciprocating saw



- Stroke: 10 mm
- 9,500 strokes per minute
- Only 0.54 kg
- Variable speed lever
- 360° adjustable exhaust
- Contains: blades (6 pieces)

4429

Reciprocating saw



- Stroke: 10 mm
- 5,000 strokes per minute
- Variable speed lever
- Piped-away exhaust system

Accessories:

P4FS-6


CCN: 45525474

Blades, 12 teeth/cm (6 pieces)

P4CS-6

CCN: 45525508

Blades, 10 teeth/cm (6 pieces)



7802SA

Air shear













- Cutting capacity:
1.0 mm (20-gauge, 0.04")
- 4,200 blows per minute

LA415-EU

Air Riveter



- Aluminum rivet capacity:
2.4 – 6.35 mm (3/32 – 1/4")
- Stroke: 16 mm

Ref.	CCN	 bpm	 mm	 kg	 mm	 in	 mm	 l/s	 l/s	 dB(A)	 m/s ² /K ⁽¹⁾
325B	49806568	4,200	–	1.0	185	1/4 NPT	10	1.9	8	96.0	15.9/1.9
529	47125885	9,500	10	0.7	246	1/4 NPT	6	0.5	1	84.3	3.1/1.0
4429	01371822	5,000	10	0.7	234	1/4 NPT	6	1.9	4	66.2	9.5/2.4
7802SA	80113681	4,200	–	1.3	239	1/4 NPT	10	1.9	10	83.0	3.0/1.0
LA415-EU	01330141	–	16	2.0	197	1/4 NPT	10	–	2	86.8	< 2.5

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Air Drills, Screwdrivers and Specialty Tools | Specialty Tools (incl. cutting tools)

LA437-EU

Air Riveter



- Aluminum rivet capacity:
2.4 – 4.75 mm (3/32 – 3/16")

LA428-EU


Caulking gun



- Power regulator
- Cartridge size: 50 x 215 mm

94058


Blow Gun



- Maximum operating pressure: 10.3 bar
- Flow 6.4 l/s
- Air inlet diameter: 1/4" BSP

LA418A-EU

Window screen Cutter



Available blades for LA418A-EU

LA418-CB1-90


LA418-CB3-30

LA418-CB7-35

LA418-CB4-8











LA418-CB6-35

LA418-CB8-24

LA418-CB2-36

LA418-CB9-60

- 20,000 strokes per minute
- Variable speed lever
- Piped-away exhaust system
- Supplied without blades
- Oscillation angle 3°

Ref.	CCN	 mm	 mm	 kg	 mm	 in	 mm	 l/s	 l/s	 dB(A)	 m/s ² /K ⁽¹⁾
LA437-EU	01328608	2.40 – 4.75	16	2.80	164	1/4 NPT	10	–	1.80	89.0	3.2/0.7
LA428-EU	01330067	–	215	1.30	356	1/4 NPT	10	–	–	70.0	2.5
94058	25011222	–	–	–	–	1/4 BSP	–	–	6.40	–	–
LA418A-EU	01336353	–	3	1.00	208	1/4 NPT	10	1.8	12.30	90.8	6.7/2.5

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.