

1/2" Cordless Impactool™, 1 057 Nm (780 lb-ft)



Convenience of Cordless. Power of Air.
The W7150EU High-Torque 1/2" Impactool™ is the only cordless impact wrench that can perform as our best-in-class 2135QXPA, 1/2" air impactool. The W7150EU cordless tool will make quick work of tough jobs that professional technicians do every day. Do the Job! Do it Fast! Do it Every Time!

- 1 057 Nm (780 ft-lb) of maximum torque and 1 486 Nm (1 100 ft-lb) of nut-busting torque, that's the best-in-class performance.
- All-metal impact mechanism and drive train provide the ultimate in durability and reliability.
- High-power rare earth magnet motor offers a long life and high power.
- Engineered composite housing for increased protection against chemical attack.
- Steel-reinforced housings add strength for unmatched drop resistance.
- Over-molded soft-touch grip minimizes vibration, reduces fatigue and enhances user comfort.
- Variable speed switch with electronic brake provides maximum control of the tool.
- Convenient one-hand operation with reverse control at trigger.
- High-capacity 5.0 Ah battery delivers maximum performance and runtime.
- Tool only is delivered without battery and charger.
 Kit K22 contains: cordless tool, charger, 2 pcs 20 V, 5.0 Ah Li-ion batteries and blow molded case.
- Kit K2 contains: cordless tool, charger, 2 pcs 20 V, 3.0 Ah Li-ion batteries and blow molded case.

Specifications

Part Number	W7150EU
Ordering number (tool only)	48391692
Part Number (kit 3.0 Ah)	W7150EU-K2
Ordering number (kit 3.0 Ah)	48391734IRI
Part Number (kit Premium 5.0 Ah)	W7150EU-K22
Ordering number (kit Premium 5.0 Ah)	47524963001
Voltage (DC)	20 V
Drive size (square)	1/2 in

PERFORMANCE

Working torque in forward	50 - 550 ft-lb / 68 - 746 Nm
Maximum torque in forward	600 ft-lb / 813 Nm
Working torque in reverse	650 ft-lb / 880 Nm
Maximum torque in reverse	780 ft-lb / 1 057 Nm
Nut busting torque in reverse	1 100 ft-lb / 1 486 Nm
Free speed	0 - 1 900 rpm
Impacts per minute	2 300

NOISE & VIBRATION

Sound pressure / power (EN60745)	89.0 / 100.0 dB(A)
Vibration level / measurement uncertainty (EN60745)	12.2 / 1.8 m/s²

WEIGHT & DIMENSIONS

Tool weight with battery	6.8 lb / 3.1 kg
Tool dimensions with battery (L x W x H)	238 x 83 x 232 mm
Shipping weight (tool only)	6.2 lb / 2.8 kg
Shipping weight (kit)	16.7 lb / 7.6 kg
Shipping dimensions (tool only) (L x W x H)	229 x 267 x 92 mm
Shipping dimensions (kit) (L x W x H)	470 x 390 x 130 mm
UPC / EAN code (tool only)	6 63024 00557 6
UPC / EAN code (Kit 3.0 Ah)	6 63024 00564 4
UPC / EAN code (Kit 5.0 Ah)	6 63024 01033 4
Origin	Made in China





SK4M3L
81287377
1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets
For the complete range, see our accessory catalogue.



W7000-CASE
48380976
Carrying case



BL2010-BOOT
47510964001
Protective battery boot BL2010/BL2022



BL2010
48386791
Li-Ion battery, 20 V, 3.0 Ah



BC1121-EU
47507874001
Universal battery charger 12/20V



0
04637336
Grease for high-speed angle heads



SK4M5L
81287369
1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



4UA9
03070216
1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)



W7150-BOOT
48401855
Protective tool boot



BL2022
47515902001
Li-Ion battery, 20 V, 5.0 Ah



L5110
48489561
Task light (without battery)



105-4T-6
04618930
Grease for Impacttools hammer mechanism (6 tubes)